Local Adaptation to Climate Change (LACC) Project Surkhet, Nepal

Time period to submit proposals 15 days April 24 - May 8, 2025

S. No.	Items Requisitioned	Unit	Quantity Required
1	Abeney Level: Consists of a fixed sighting tube, a movable spirit level connected to a pointing arm, 1 1/8" radius arc graduated from 0 to 90 degrees in both directions, with vernier reading to 10 minutes, and percent of grade scale from 0 to 100 percent. Measures 5 1/8" long and comes complete with a belt loop case.	рс	12
2	Measuring tape (steel) -5 m :5 meters (or 16.4 feet), width: - typically between 12.5mm to 19mm, Material: stainless or carbon) Graduation: typically in millimeters or centimeters, With Blade coating, Locking mechanism:	рс	12
3	Measuring tape (fiber glass)-30 m :Dimensions: 17 x 17 x 3.8 Centimeters, Item Weight 331 Grams, Blade Material: Fiberglass, Blade Length: 30 Meters with VC housing with ergonomic handle	рс	12
4	Portable Projector: Full HD portable projector featuring a resolution of 1920x1080P and 3000 lumens of brightness, delivering clear and vibrant visuals. It supports both 16:9 and 4:3 aspect ratios for versatile viewing. Powered by 1GB DDR3 RAM, it operates on an AC 100V–240V, 50/60Hz power supply, consuming 45W. Chargeable battry, Compact and lightweight, the projector measures 19.5 x 17.5 x 16.5 cm and weighs 1.66 kilograms, making it easy to carry and ideal for on-the-go use. Finished in sleek black, it combines portability with performance.	рс	5
5	GPS Device: Sunlight Readable 2.6 inch color display; Expanded Internal Memory 4GB. Display type is transflective, 65k color tft; Display resolution is 160 x 240 pixels. DUAL BATTERY SYSTEM Use with 2 traditional AA batteries, or the optional rechargeable NiMH battery pack that can be charged while inside the device.Weight 8.1 ounce (230 gram) with batteries: AA batteries required (best with Polaroid AA batteries). Receive Smart Notifications* and pair with optional ANT+ sensors, such as heart rate monitor, Tempe temperature sensor, speed/cadence, or use to control your VIRB action camera (64s/64st only). Wireless upload data to Connect and view on smartphone, plus share activities as they happen with Live Track (64s/64st only).Display size(inches):1.43 x 2.15	рс	12
6	Scientific Calculators: Acrylonitrile butadiene styrene (ABS) materials having a keypad, an input line, a preview area, and a group of buttons for inserting special mathematical elements.The minimum capabilities of a scientific calculator: scientific notation, floating-point decimal arithmetic, logarithmic functions, using both base 10 and base e, trigonometric functions (some including hyperbolic trigonometry), exponential functions and roots beyond the square root, quick access to constants such as pi and e etc.	рс	13

8	 TRANSPONDER T3 Size: Diameter 70 mm/2,8" Weight: 85 g/5 oz (Incl. Battery) Battery: 1.5V AA alkaline Consumption: max 9mW Big Size Printer: Trays with stands B 7135 Digital Copy/Print/Scan (Color) # Model: B7135 Digital Copy/Print/Scan # Type: System on Wheels # Monthly Duty Cyc1e: 153,000 images/month # Control Panel: 7 inch Color Touch Screen # Paper Capacity: Tray 1 x 520 sheets + 100 Sheets By Pass # Tray 2 x 520 sheets with Storage Stand # Paper Output: Single Catch Tray : 500 sheets # Processor: 1.05 GHz Dual Core # Memory : 4 GB # Copy/Print Speed: 35 cpm A4 # Copy/Print Size: A5 to A3 # Multiple Copying : 1-999 copies # Reduction Ratio: 25-400% in1% increment/decrement # First Copy Time: 4.3 Sec. # Single Pass Duplex Automatic Document Feeder : 130 sheets # 10/100/1000 BaseT, USB 3.0, # Mobile Printing: Standard # Network Print & Color Scan, Scan to Email/Network/Folder /USB 	Sets	1
7	VERTEX 5 Size: 80x54x31mm (3,14"x2,12"x1,22") Weight: 173 g (6.10 oz.)(incl. battery) Battery: 1 x 1,5 AA alkaline, Current 20mA with Bluetooth 150mA Temperature: -20° to +45°C / -4°F to 113°F Wireless interface: Bluetooth 4.0 (BLE), IR Memory Storage 5000 data sets. Signal: Built-in loud speaker Ultra sonic frequency: 25 kHz Height: 999 m (3277 ft.). Resolution: 0.1 m/ 0.1 ft Angles: -90° to +90° deg./ -100° to +100° grads, Resolution: 0.1° Distance: 30 m / 100 ft. With 360° adapter 20 m / 60 ft . Resolution: 0.01 m/ 0.1 ft Accuracy: 1% BAF factors: 0.5, 1 to 9 (m2/ha) or 5, 10, 15to 50 (ft2/acre) Languages settings: Czech, Danish, English, Estonian, Finnish, French, German, Italian, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Russian, Spanish and Swedish.	Sets	1